SILOGRAM LUBRICANTS CORP.

Full Strength Antifreeze

Full strength Antifreeze, 55 gallon drum.

Mfg. No.	PG No.
	ANTIFR-55

OLD WORLD AUTOMOTIVE INDUSTRIES

PEAK Long Life Antifreeze & Coolant

PEAK Long Life Antifreeze & Coolant features a LongLife coolant technology that is compatible for use in all automobiles and light duty trucks, regardless of make, model, year or original antifreeze color.

- Compatible for use in all automobiles and light duty trucks
- Amber color will not change the current antifreeze color when used for topping off
- Provides 150,000 miles or 5 years of maximum protection when a complete cooling system flush and fill is performed
- Features a phosphate-free and silicate-free formula
- Meets ASTM D-3306 and ASTM D-4340

Mfg. No.	PG No.
PKA003	ANTIFREEZE

TRUSERV

Portable Barrel Fan



36 in. Portable Barrel fan

Features:

- Belt drive air circulator
- 4 blades for smooth air flow
- 1/3 HP motor
- 6 in. pneumatic wheels
- 8 ft. power cord
- Air Movement: 10,200 CFM
- UL Listed
- Meets OSHA Standard 1910.212

Mfg. No.	PG No.
PINNACLE 718245	FAN-36

AIR KING LIMITED

Wall Mount Fan

24 in. Oscillating Wall Mount Fan (90° oscillation)

- Motor: 3-speed, 1/4 HP, 120V, 1 phase, totally enclosed, ball bearing, permanently lubricated, permanent split capacitor
- Controls: Rear mounted pull cord switch
- Power Cord: Black, 10', 3-conductor, SJT type
- Coating: Blade, Guard, and Mounts are Powder coated steel
- Compliance: ETL, OSHA

Mfg. No.	PG No.
9025	FAN-W24

LASKO

Box Fan

Step up to the premium, 20 in. box fan and enjoy the benefits of the Wind Ring™ system, an exclusive grill design that focuses the air movement, increasing its velocity

- Three, whisper-quiet speeds
- 30% More air velocity than most standard box fans
- Energy-efficient, high volume air movement
- Wide-body design for stability

Mfg. No.	PG No.
3723	FAN-20

AIR KING LIMITED

Circulator Fan

Floor



Heavy duty, 24 in. floor circulator fan

Mfg. No.	PG No.
9224	FAN-24

LASKO
Clip Fan



6 in. White, Rotating Clip On Fan

- For added versatility, the fan head can rotate a full 360 degree to direct air precisely where it is needed most
- Two, whisper-quiet speeds with easy-grip rotary control
- Spring-loaded clip clamps onto objects 3/4 in. to 1 - 3/8 in. wide
- Durable, impact-resistant plastic construction
- Easy to assemble - no tools required

Mfg. No.	PG No.
2004W	FAN-06

AIR KING LIMITED
Pedestal Fan
Oscillating

Three, Whisper-Quiet Speeds

- Full 90 degree Oscillation or Stationary Cooling
- Fully Adjustable Height (37 in. to 53 in.) for Maximum Versatility
- Adjustable Tilt-Back to Direct Air Where Needed
- Energy-Efficient Operation
- Simple Assembly Required
- U.L. Listed

Mfg. No.	PG No.
2526	FAN-PED-16

AIR KING LIMITED
Pedestal Fan
Industrial

- 2 speed, 1/4hp, 115 volt, ball bearing totally enclosed, permanently lubricated permanent split capacitor motor with pull chain switch
- 3 conductor SJT type cord
- 3 blade coated steel fan
- Double locking chrome plated guard
- 15 deg. up or down fan head tilt
- Column adjusts from 48 7/8 in. to 74 5/8 in.
- 27 in. steel dome pedestal base

Mfg. No.	Desc.	Blade Diameter(in.)	PG No.
9124	Pedestal, Non-Oscillating	24	FAN-PED
9130	Pedestal, Non-Oscillating	30	FAN-PED-30
9125	Pedestal, Oscillating	24	FAN-PED-1
9135	Pedestal, Oscillating	30	FAN-PED-30X

LASKO
Table Fan

Table Fan. An advanced grill design, soft white body, copper and chrome accents and six-position pivot all blend together to create the ultimate in room cooling comfort. Optional oscillation allows widespread comfort, while a compact design provides go-anywhere versatility

- Three, whisper-quiet speeds
- Full 90 degree oscillation or stationary cooling
- Six-position pivot to direct air where needed
- Energy-efficient operation
- Simple assembly required - grills snap together

Mfg. No.	Size (in.)	PG No.
2508	9	FAN-09
2500	12	FAN-12
2506	16	FAN-16

LASKO
Wall-Mount Fan
Oscillating

Wall-mount fans are real problem-solvers. They can be quickly installed with the included mounting hardware, and they can be controlled by either the rotary knob or the three-way pull cord, making higher installations practical

- Three, whisper-quiet speeds with optional oscillation
- 3-Prong, grounded plug durable, impact-resistant plastic construction
- Easy to assemble - no tools required

Mfg. No.	Size (in.)	PG No.
3012	12	FAN-W12
3016	16	FAN-W16

PRECISIONAIRE

Hammock Filter Roll

240 x 1 in. Spun Fiberglass Hammock Filter, Roll.

Mfg. No.	Size (in.)	PG No.
HR24240	24	AF-R24
HR30240	30	AF-R30
HR36240	36	AF-R36

Air Filter
Pleated

Pleated Air Filter, 1 in. Thick, Case Pack: 12.

Mfg. No.	Nominal Size(in.)	PG No.
600-702	10 x 20 x 1	AF-P10201
600-724	12 x 20 x 1	AF-P12201
600-736	12 x 24 x 1	AF-P12241
602-795	14 x 14 x 1	AF-P14141
600-744	14 x 20 x 1	AF-P14201
600-757	14 x 24 x 1	AF-P14241
600-765	14 x 25 x 1	AF-P14251
600-773	15 x 20 x 1	AF-P15201
602-803	16 x 16 x 1	AF-P16161
600-815	16 x 20 x 1	AF-P16201
645-406	16 x 24 x 1	AF-P16241
600-823	16 x 25 x 1	AF-P16251
600-835	20 x 20 x 1	AF-P20201
600-843	20 x 25 x 1	AF-P20251
600-856	20 x 30 x 1	AF-P20301
600-864	24 x 24 x 1	AF-P24241

Air Filter
Pleated

Pleated Air Filter, 2 in. Thick, Case Pack: 12.

Mfg. No.	Nominal Size(in.)	PG No.
338-111	16 x 20 x 2	AF-P16202
275-633	16 x 25 x 2	AF-P16252
275-746	20 x 20 x 2	AF-P20202
294-014	20 x 25 x 2	AF-P20252
714-657	25 x 25 x 2	AF-P25252

Air Filter
Foam

15 in. x 24 in. x 1/4 in. Foam Air Conditioner Filter, Trim to Size,

- Case Pack: 24.

Mfg. No.	PG No.
F1524	AF-FOAM

Air Filter
Fiberglass

Fiberglass Air Filter. Double-Skinned Media for Stronger Filters: Our double-skinned media is stronger than ever. Using a computer-automated manufacturing process, a fiberglass retainer is spun on both sides of the media. The strength is built into the fiberglass, eliminating the need for scrim or metal type retainers. Disposal is convenient and safer because there are no sharp metal edges.

Durable Frames Decrease Handling Damages: Bonded with glue, the double-skinned fiberglass retainer adheres securely to the chipboard frame, providing durability, less handling damage and longer shelf life. Case Pack: 12.

Mfg. No.	Nominal Size(in.)	PG No.
504-597	8 x 16 x 1	AF-08161
726-754	10 x 10 x 1	AF-10101
266-486	10 x 20 x 1	AF-10201
114-986	10 x 24 x 1	AF-10241
114-994	10 x 25 x 1	AF-10251
263-434	12 x 12 x 1	AF-12121
323-774	12 x 20 x 1	AF-12201
300-673	12 x 24 x 1	AF-12241
115-003	12 x 25 x 1	AF-12251
115-033	12 x 27 x 1	AF-12271
109-713	12 x 30 x 1	AF-12301
115-052	12 x 36 x 1	AF-12361
263-129	14 x 14 x 1	AF-14141
266-478	14 x 20 x 1	AF-14201
584-219	14 x 24 x 1	AF-14241
266-460	14 x 25 x 1	AF-14251
439-083	14 x 30 x 1	AF-14301
266-452	15 x 20 x 1	AF-15201
115-066	15 x 25 x 1	AF-15251
439--109	16 x 16 x 1	AF-16161
266-445	16 x 20 x 1	AF-16201
440-586	16 x 20 x 2	AF-16202
439-091	16 x 24 x 1	AF-16241
266-437	16 x 25 x 1	AF-16251
440-594	16 x 25 x 2	AF-16252
343-848	16 x 30 x 1	AF-16301
312-066	18 x 18 x 1	AF-18181
312-322	18 x 20 x 1	AF-18201
312-736	18 x 24 x 1	AF-18241
726-762	18 x 24 x 2	AF-18242
440-578	18 x 25 x 1	AF-18251
115-086	19 x 27 x 1	AF-19271
266-429	20 x 20 x 1	AF-20201
440-602	20 x 20 x 2	AF-20202
312-504	20 x 24 x 1	AF-20241
266-411	20 x 25 x 1	AF-20251
475-392	20 x 25 x 2	AF-20252
440-628	20 x 30 x 1	AF-20301
344-267	22 x 22 x 1	AF-22221
584-235	24 x 24 x 1	AF-24241
726-776	24 x 24 x 2	AF-24242

Mfg. No.	Nominal Size(in.)	PG No.
584-243	24 x 30 x 1	AF-24301
731-497	24 x 36 x 1	AF-24361
440-560	25 x 25 x 1	AF-25251

Air Filter
Fiberglass

15 in. x 24 in. x 3/8 in, Fiberglass Air Conditioner Filter, Trim to Size.

- Case Pack: 24.

Mfg. No.	PG No.
KK600	AF-FIBER

PRECISIONAIRE
Hog Hair Filter

25 in. x 30 ft. x 1 in, Hog Hair Washable Furnace Filter, Latex Coated Coconut Fiber, For Medium Furnace & Central Air, Cuts To Fit, Rigid & Ready To Install, Needs No Frame.

Mfg. No.	PG No.
HHB25130	AF-RH25

SUNBEAM PRODUCTS
Electric Heater
Ceramic

Holmes, Ceramic Heater With 2 Settings, 1000/1500W & Thermostat, Internal Shroud, Adjustable Tilt, Swivel, Top Rear Controls, Auto Safety Shut Off, BTU's: 3412 At Low & 5118 At High, Item Dimensions: 11.5 in. H x 11 in. W x 6.75 in. D.

Mfg. No.	PG No.
HCH4163	H-CERAMIC

PEARLGREEN
Kerosene Forced Air Heater

Duraheat, Kerosene Portable Forced Air Heater With Thermostat, Built In Fuel Gauge, Convenient Drain Plug, On/Off Switch, Includes UL Listed Large Capacity Motors and Fuse Protected Electrical System, All Components Are Securely Fastened Into Chassis To Insure Long Life, Utilizes Heavy Duty Spark Technology For In Field Endurance.

Mfg. No.	BTUs	Coverage (sq. ft.)	Fuel Tank Size (gal.)	PG No.
DFA125T	125,000	2800	10	H-KERO-T125
DFA170C	175,000	4000	13	H-KERO-T170
DFA210C	210,000	4800	13	H-KERO-T210

WORLD MARKETING OF AMERICA
Kerosene Heater
23,000 BTU

Kero-World, 23,000 BTU, Convection Style Kerosene Wick Heater, Easy To Assemble Design, Easy Install Safety Cage, Drip Tray, Heats Approximately, 1,075 SQFT, Operates Without Electricity.

Mfg. No.	PG No.
KW24G	H-KERO-23

MARLEY
Electric Heater
Portable Baseboard

- It is an 100% energy efficient. Heat is dissipated by large fins into a strong convection flow. This delivers every bit of available heat
- Distinctively designed. High-impact lexan end panels with built-in handles. Low profile designs enhances the unique appearance and add to the units overall stability
- The complete heating cycle fills your entire room with uniform, gentle floor-to-ceiling warmth and comfort
- Safety thermal cutout protection
- UL Listed
- Heater Volts: 120, Watts: 1500, BTU/HR: 5120, Current Rating: 12.5 A, Length: 45 in., Height: 7 - 1/2 in., Depth: 5 - 1/2 in.

Mfg. No.	Wattage	PG No.
FBE15002	1500/900/400	H-BB

JARDEN CONSUMER - HEATER

Heater

1000/1500 BTUs

Westpointe, Gray, Milkhouse Heater, 1000/1500W, BTU's: 3412 At Low, 5118 At High, Heavy Duty Electric Utility Heater, Automatic Thermostat, Fan Forced Convection Coils, Special Handle For Easy Mobility, Tip Over Protection, Auto Shut Off, Overheat Protection, Manual Reset, Overhead Mounting, Item Dimensions: 16 in.H x 10 in.W x 6 in.D.

Mfg. No.	PG No.
WUH680-UM	H-1500

MARKEL PRODUCTS

Portable Heaters

HEAT WAVE™

- Safety yellow heater enclosure with safety screens on both air intake and output openings
- Optional 25' long SO type cord, ready for plug attachment is available for each model
- Long-life finned tubular heating elements
- Thermostat adjustments 40 deg. to 100 deg. F
- Magnetic contactor
- Automatic reset
- High-limit thermal cutout switch
- Fan only switch
- 10 in. wheels
- 800 CFM - 15 KW units - 1100 CFM - 30 KW units, BTU's: 51195, Volts: 240, PH: 3, Amps: 36, Temperature Rise: 45 deg. F, KW: 15

Mfg. No.	PG No.
FES-1524-3E	H-1524

MARKEL PRODUCTS

Electric Heater

Portable

Combination of both radiant and forced heater

- 3-Heat Settings: 600 watt radiant, 900 watt fan forced
- Temperature control thermostat
- Dual safety system: Tip over switch, manual reset type limit control
- 6 ft. long - 3 conductor cord
- MAX BTU's, Volts: 120, Single Phase, Width: 11 in., Height: 15 in., Depth: 12 in., UL listed
- Code: 9399

Mfg. No.	Wattage	PG No.
198TMC	1500	H-198

MARKEL PRODUCTS

Portable Heaters

- Operates on 240 V or 208 V
- Fined steel tubular heating element
- Internal manual reset thermal cut-out
- 6 ft. long cord with molded plug
- 10 ft. air throw - 262 CFM
- Single Phase, MAX BTU's: 19107 / 14330, Amps: 23.4 / 20.2, Temperature Rise: 75 deg. F, UL listed.
- Wattage: 5600

Mfg. No.	PG No.
HF-686TC	H-686

DESA INTERNATIONAL

Propane Heater

75-150-200,000 BTU, Convection Style LP Heater, Projects Heat 360 Degrees, Knock Down Chamber Provides Easy Portability, Matchless Piezo Ignition, No Electricity Required, Heats Approximately 4700 SQFT, Operates 17 Hours On Single 100 LB Cylinder, Sold Separately, Perfect For Drywall, Painting & Concrete Curing, Ideal For Professional and DIY Construction Projects.

Mfg. No.	PG No.
RCP200VA	H-PROP

MARKEL PRODUCTS

Utility Heaters

- Operates on 240 V or 208 V
- Steel tubular heating element
- 43 deg. F air heat rise
- Internal overheat thermostat
- Temperature control thermostat
- 6 ft. long cordset
- Single Phase, MAX BTU's: 13648, Width: 10 5/8 in., Height: 12 3/4 in., Depth: 10 in., cULus listed.
- Wattage: 4000

Mfg. No.	PG No.
ICH-240C	H-240

WORLD MARKETING OF AMERICA
Replacement Wick

23,000BTU Heater Wick

Mfg. No.	PG No.
32225	WICK-23

MIDEA AMERICA CORP.
Electric Heater
Oil Radiator

Westpointe, Oil Filled Convection Radiator Electric Heater

- 3 Heat Settings
- 600W, 900W & 1500W
- Thermostat, Wheels
- Built In Cord Storage
- ETL Approved
- Item Dimensions: 13.78 in.L x 9.84 in.W x 25.79 in.H
- Weight: 21.2 lbs.
- Code: 9189

Mfg. No.	PG No.
NY15AH	H-RAD

CONVENIENCE PRODUCTS
Insulating Expand Foam

Touch 'N Foam, 12 oz., Triple Expansion Insulating Foam, Reusable Dispensing System, Patented All Direction Dispensing, Full Expansion Foam To Fill Holes & Voids, Seals & Insulates, Bonds To Most Surfaces, Tack Free In 30 Minutes, Can Be Sanded Or Painted Within & Hour.

Mfg. No.	PG No.
4001152120	FOAM

J&S INSULATION
Insulation Foil

Foil faced insulation is engineered to provide an extremely effective, low-cost system to help keep BTUs where they belong: outside when it's hot, and inside when it's not.

Mfg. No.	Size (in.)	PG No.
	16	FOIL-16
	24	FOIL-24

JOHNS MANVILLE
Insulation



Fiberglass Pipe Insulation

Mfg. No.	Size (in. x ft.)	PG No.
MICRO-LOK 1/2" WALL	½ x 3	PI-01
MICRO-LOK 1/2" WALL	¾ x 3	PI-02
MICRO-LOK 1/2" WALL	1 x 3	PI-03
MICRO-LOK 1/2" WALL	1¼ x 3	PI-04
MICRO-LOK 1/2" WALL	1½ x 3	PI-05
MICRO-LOK 1/2" WALL	2 x 3	PI-06
MICRO-LOK 1/2" WALL	2½ x 3	PI-07
MICRO-LOK 1/2" WALL	3 x 3	PI-08
MICRO-LOK 1/2" WALL	3½ x 3	PI-09
MICRO-LOK 1/2" WALL	4 x 3	PI-10
MICRO-LOK 1/2" WALL	4½ x 3	PI-11
MICRO-LOK 1/2" WALL	5 x 3	PI-12
MICRO-LOK 1/2" WALL	6 x 3	PI-13
MICRO-LOK 1/2" WALL	8 x 3	PI-14

EAGLE MANUFACTURING CO.
Rubber Pipe Insulation

Sold in 6 foot lengths. Inhibits condensation from water lines, while providing substantial insulation. Not for use on temperatures over 130 degrees F.

Mfg. No.	Width (in.)	PG No.
ARMA-CELL#APT07812	1/2	PI-R01
ARMA-CELL#APT11812	3/4	PI-R02
ARMA-CELL#APT13812	1	PI-R03
ARMA-CELL#APT15812	1 1/4	PI-R04
ARMA-CELL#APT11012	1 1/2	PI-R05
ARMA-CELL#APT20012	2	PI-R06
ARMA-CELL#APT21812	2 1/8	PI-R06A
ARMA-CELL#APT21012	2 1/2	PI-R07
ARMA-CELL#APT30012	3	PI-R08
ARMA-CELL#APT41812	3 1/2	PI-R08A
ARMA-CELL#APT	4	PI-R09
ARMA-CELL#APT50012	5	PI-R10
ARMA-CELL#APT60012	6	PI-R11

WRAP-ON CO.

Wrap On Pipe Insulation

- Superior thickness & density
- Offers complete pipe protection
- High tensile strength
- Easy installation
- For all hot and cold water pipes
- Comes with Vapor Seal Wrap

Mfg. No.	PG No.
WRAP-ON#16503	PI-W

ITP

Backer Rod

Basic use: ITP standard backer rod is an ideal non-absorbent compressible backup material. It is inserted into a joint to control sealant depth to create a backstop to:

- Allow proper sealant tooling
- Allow proper sealant wetting of the joint surfaces
- And yield a proper bond breaker between the backer rod and sealant

Mfg. No.	Diameter (in.)	Feet per Carton	Meters per Carton	PG No.
STANDARD	¼	8000	1219	BACKER-1C
STANDARD	⅜	4200	640	BACKER-2C
STANDARD	½	2500	762	BACKER-3C
STANDARD	⅝	1550	472	BACKER-4C
STANDARD	¾	1100	335	BACKER-5C
STANDARD	1	600	182	BACKER-6C
STANDARD	1¼	400	121	BACKER-7C
STANDARD	1½	1050	128	BACKER-8C
STANDARD	2	600	73	BACKER-9C

DAP

Latex Foam Sealant

Daptex, 12 oz., Latex Foam Sealant, Water Based, Water Clean Up, Easy To Use Insulating Foam, Toolable, Moldable, Flexible, Durable Seal, Controlled Expanding Foam, Reusable Product, No Mess, Paintable, Interior/Exterior Use.

Mfg. No.	PG No.
18826	DAPTEX

I.D.C

Styrofoam



Lightweight, tough, durable, ideal for crafting terrain such a hills and cliffs, making gaming boards, even buildings and bases. It doesn't warp, is relatively light and can be worked easily with a hot-wire cutter, hot-knife, sawn and even cut with a sharp knife.

Mfg. No.	Size (HxLxW)	PG No.
DOW/STYROFOAM/SQ	2'x8'x1"	STYRO-1
DOW/STYROFOAM/SQ	4'x8'x1"	STYRO-1A
DOW/STYROFOAM/SQ	2'X8'X2"	STYRO-2
DOW/STYROFOAM/SQ	4'X8'X2"	STYRO-2A

J&S INSULATION
Thermafiber
Thermafi ber® SAFB™



THERMAFIBER Sound Attenuation Fire Blankets (SAFB) are mineral wool batts designed to stop sound, save energy, and provide life saving fire protection. These products are noncombustible, moisture-resistant, noncorrosive, nondeteriorating, mildew-proof and verminproof. Thermafiber SAFBs provide acoustical control, thermal insulation, and fire protection in many different UL fi re rated wall and floor-ceiling assemblies. SAFBs resist temperatures over 2000ºF as compared to fiberglass insulation that melts around 1000ºF. SAFBs add STCs to wall and fl oor-ceiling assemblies. SAFBs can be installed in both steel stud and wood stud construction.

- Exceptional sound and noise absorption
- Excellent Thermal Performace (R-value of 3.8 per inch.)
- Adds STC value to wall and floor-ceiling assemblies.
- Provides life saving fire protection in rated assemblies
- Fire resistant to temperatures above 2,000°F (1,093°C)
- Conserves energy, reduces Greenhouse gas and carbon emissions
- Mold resistant

Mfg. No.	Width (in.)	PG No.
THERMAFI-BER#SAFB-2”	2	THERM-2
THERMAFI-BER#SAFB-4	4	THERM-4

TAYLOR USA
Pocket Stem Thermometer

The Taylor 6072N superior grade dial thermometer gives a clear analog reading with its 1 in. dial. It has 3 point calibration that allows for + / - 1% accuracy at any point. With an accuracy range of 0 to 220 degrees Fahrenheit, you can be sure that this is the perfect probe thermometer for your kitchen. Its 5 in. stainless steel stem and unbreakable polycarbonate crystal lens ensure the toughest durability. It can be recalibrated with its Safe-T-Set wrench, which is built into the carrying case! Suitable for lab use as well.

Mfg. No.	PG No.
TAY-LOR#6072N	TH-6072

TAYLOR USA
Swing Thermometer

Indoor/Outdoor Metal Thermometer. Mount on wall using the two screws included. For the most accurate temperature readings choose a location that will not be exposed to direct sunlight. 3.50 inches tall x 3.50 inches long x 1.00 inches wide.

Mfg. No.	PG No.
	TH-SWING

TAYLOR USA
Digital Thermometer

A Taylor thermometer that's a step up in functionality is the Taylor 9841. It has the capability of reading a higher temperature range (-58 to 500° F, -50 to 260° C), and is accurate to within 1/10th of a degree up to 199.9 degrees F. This thermometer has an on-off switch to extend the life of the battery. It also has a switch that allows the 1/3 inch display to read in degrees Fahrenheit or Celsius.

Mfg. No.	PG No.
TAY-LOR#9841	TH-9841

EXTECH INSTRUMENTS
Infrared Thermometer

Compact thermometer measures up to 500°F (260°C)

- Built-in laser pointer identifies target area
- Backlighting illuminates display for taking measurements at night or in areas with low background light levels
- Automatic Data Hold when trigger released
- Fixed 0.95 emissivity covers 90% of surface applications
- Auto power off

Mfg. No.	PG No.
42500	MINITEMP

TAYLOR USA
Indoor/Outdoor Thermometer

The Taylor 5329 is a traditionally styled analog thermohygrometer. The 5329 measures the indoor humidity, indoor temperature, and also the outdoor temperature via its wired probe. With its large, easy-to-read face, and its classic design, the Taylor 5329 would serve well in both home and work environments.

Mfg. No.	PG No.
TAY-LOR#5329	TH-5329

TAYLOR USA

Wall Thermometer

Taylor

This Taylor Precision 5154 thermometer comes with an attractive, granite look, an easy to read face and recessed tube. It has a temperature range from 0 degrees Fahrenheit to 120 degrees Fahrenheit. It reads in Fand C. It includes an aluminum bracket for secure wall mounting. It is weather resistant and rust proof. 7 5/8 in. high x 2 3/8 in. wide.

Mfg. No.	PG No.
TAY-LOR#5154	TH-5154

TAYLOR USA

Window Thermometer

Window/Wall Thermometers Type: Indoor/ Outdoor Thermometer Minimum Temperature (°F): -40.000 Maximum Temperature (°F): 120.000

Mfg. No.	PG No.
TAY-LOR#5316	TH-5316

MEPCO/DUNHAM BUSH

Steam Trap

Mepco industrial thermostatic traps are recommended where air handling is critical. They handle steam, air, and condensate by pressure and temperature to open and close the diaphragm or bellows. The thermostatic element expands when steam is present to close the trap, and contracts when the cooler air or condensate is present to open the trap which allows the condensate to drain. The Mepco thermostatic trap has a cast bronze body and is available in angle or straight pattern.

Mfg. No.	Size	Desc.	PG No.
1E-AP	½	1E Angle Trap	TP-D1A
1E-SW	½	1E Straight Trap	TP-D1
2E-AP	¾	2E Angle Trap	TP-D2A
2E-SW	¾	2E Straight Trap	TP-D2
C5940	½	1E Replace-ment Disc	TP-DD1
C5941	¾	2E Replace-ment Disc	TP-DD2
C5838	½	1E Disc and Cap	TP-DDC1

ALB INDUSTRIES

Steam Trap

Thermo-Dynamic steam traps combine reliability, simplicity and efficiency of operation. With just one moving part - a hardened stainless steel disc - they give a blast discharge with clean, tight shut-off. They're able to withstand superheat, waterhammer, corrosive condensate, freezing and vibration. The TD trap is the first choice for removal of condensate from steam distribution systems.

Mfg. No.	Size (in.)	Desc.	PG No.
SARCO #RTA-125	1/2	Angle Steam Trap	TP=SA12
SARCO #RTA-125	3/4	Angel Steam Trap	TP-SA34
SARCO #RTH-125	1/2	Straight Trap	TP-SH12
SARCO #RTH-125	3/4	Straight Trap	TP-SH34
SACRO# TDC52	1/2	Steam Trap	TP-STD12
SARCO# TDC52	3/4	Steam Trap	TP-STD34

THERMWELL

Foam on Wood Door Set

Door set includes 2 strips 1 1/2 in.W. x 7 ft. L., and 1 strip 1 1/2 in.W x 3 ft.L. Unfinished wood with white vinyl clad foam can be nailed in place around wood framed doors, then stained or painted to match the home decor. It can be installed on the door stop.

Mfg. No.	PG No.
THERM-WELL#ND-1	MORTEX

THERMWELL

Mortell No-Drip Pipe Coating

- Insulates hot water pipe against heat loss up to 160 Degrees Farenheit.
- Wont dry out, crack or shrink.
- No special tool or adhesive is needed.
- Stops condensation on cold water pipes, cooling and refrigeration lines

- Non absorbent, moisture proof, wont root or saturate.

Mfg. No.	PG No.
THERM-WELL#NDT 130	NO-DRIP

THERMWELL

Weather Strip and Caulking Cord

Thermwell

Caulk putty effectively seals windows and more. Used widely as a gasketing material, sound deadener, insect barrier, and crack filler. Pliable, just peel and press into place with fingertip. Will not crack or harden.

Mfg. No.	PG No.
THERM-WELL#B-2	MORTITE

TAPE-RITE

Foam Weatherstrip



- Closed cell PVC foam tape
- Waterproof Self stick
- Moderate compression
- Fills even irregular gaps
- Interior or exterior use

Mfg. No.	Thickness (in.)	PG No.
TAPE-RITE#4763	1/4X1/4	WS-1
TAPE-RITE#4763	3/8X1/4	WS-2
TAPE-RITE#4763	1/2X1/4	WS-3
TAPE-RITE#4763	3/4X1/4	WS-4
TAPE-RITE#4763	1X1/4	WS-5

THERMWELL

Window Weatherstrip



- Open Cell Foam Tape
- For Weather-Stripping Around Window Air Conditioners
- Compressible Strip For Sealing Out Air

Mfg. No.	Thickness (in.)	PG No.
THERM-WELL#AC1	1 1/4	WS-AC1
THERM-WELL#AC2	2 1/4	WS-AC2

GILMOUR GROUP

CLR Thermostat Cover



Clear Plastic Thermostat Guard Cover, 6-1/2 H, 7-1/2 in. W, 2-15/16 in. D, Fits Replacement Thermostats, Carded.

Mfg. No.	PG No.
CG511A1000	THERM-C1

HONEYWELL CONSUMER

Locking Thermostat Cover

Locking Thermostat Guard Cover, 9-3/4 in. W, 7-1/8 in. H, 3-3/8 in. D, Carded.

Mfg. No.	PG No.
CG512A1009	THERM-C2

Drain Pan

Anti-Clog

For Air Conditioning Drain Pan Maintenance and Health Protection. Improved dispenser allows more effective action! Biocide inhibits the growth of harmful bacteria, including those causing the deadly Legionnaire's disease, the common cold, asthma, fatigue, headaches, flu and allergies. Also controls condensate pan flooding due to growths of slime and algae stopping up the drain. Total drain pan protection that works either horizontally or vertically

- Keeps drain pans clear, preventing pan overflows
- Reduces odors by eliminating slime bacteria waste
- Long lasting
- Easy to install
- Allows for placement either in pan or on the side of the coil
- Effective against Legionella
- Inhibits corrosion in drin pans
- Contains no foaming detergents
- Size: 5- 15 tons

Mfg. No.	PG No.
FT-C	ANTICLOG

914-636-0505 Phone
914-636-8951 Fax

Dryer Vent Clamp



Metal Vent Clamp,Size: 4 in.

Mfg. No.	PG No.
0812008	DRYER-H-C

Dryer Vent Kit

Size x Length: 4 in. x 8 ft., Plastic, Master Carton: 15

Mfg. No.	PG No.
0811004	DRYER-4